Datasheet




# intAct Bike-Power Classic

Low-maintenance lead-acid battery | dry-charged, acid pack included | low maintenance

Art.No.

## 01225S

Japancode

6N12A-2C, 6N12A-2D, B54-6A, B54-6

| | |
|---|---|
| **Volt** | 6V |
| **Capacity** | 12 Ah (c20) |
| **CCR -18°C (EN)** | 80 A (EN) |
| **Electrolyte** | diluted sulphuric acid |
| **Electrolyte density** | 1,28 +/- 0,01 kg/l (25°) |
| **Size (LxWxH)** | 156 x 57 x 116 mm |
| **Weight** | 2,1 kg |
| **Pos. of Terminal** | **1** |
| **Terminal** | **B** |
| **Entgasung** | **4** |

**Usage**

## Powerful and sustainable

The solid battery without frills delivers high starting power, with regular maintenance it achieves a long service life and has excellent recycling properties. Our recommendation for an inexpensive standard motorcycle battery.

- **Reliable starting power at an excellent price.**
- **Replacement recommendation** for broken flooded battery.
- **Central degassing.**
- **Only to be installed upright,** as flooded battery with vent caps.

**Size**




**Pos. of Terminal 1**



**Terminal B**




**Entgasung 4**




As of 24.11.2026

KECKEISEN AKKUMULATOREN
**Stefan Keckeisen Akkumulatoren e.K.**
Europastraße 9
87700 Memmingen
Fon +49(0)8331 94444-0
Fax +49(0)8331 94444-9
info@intact-batterien.de
www.intact-batterien.de