Datasheet



intAct Bike-Power Classic

Low-maintenance lead-acid battery | dry-charged, acid pack included | low maintenance

Art.No.

50411S

Japancode

YB4L-B

Volt	12V
Capacity	4 Ah (c20)
CCR -18°C (EN)	20 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28+/- 0,01Kg/l (25°)
Size (LxWxH)	120 x 70 x 92 mm
Weight	1,7 kg
Pos. of Terminal	**0**
Terminal	**A**
Entgasung	**3**

Usage

Powerful and sustainable

The solid battery without frills delivers high starting power, with regular maintenance it achieves a long service life and has excellent recycling properties. Our recommendation for an inexpensive standard motorcycle battery.

- **Reliable starting power at an excellent price.**
- **Replacement recommendation** for broken flooded battery.
- **Central degassing.**
- **Only to be installed upright,** as flooded battery with vent caps.

Size



Pos. of Terminal 0



Terminal A



Entgasung 3



As of 23.11.2026

KECKEISEN AKKUMULATOREN
Stefan Keckeisen Akkumulatoren e.K.
Europastraße 9
87700 Memmingen
Fon +49(0)8331 94444-0
Fax +49(0)8331 94444-9
info@intact-batterien.de
www.intact-batterien.de