Datasheet



intAct Bike-Power Classic

Low-maintenance lead-acid battery | dry-charged, acid pack included | low maintenance

Art.No.

52420S

Japancode

12N24-4, Y60-N24-A

Volt	12V
Capacity	24 Ah (c20)
CCR -18°C (EN)	220 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 kg/l (25°)
Size (LxWxH)	186 x 125 x 176 mm
Weight	8,5 kg
Pos. of Terminal	**1**
Terminal	**G**
Entgasung	**6**


Usage

Powerful and sustainable


The solid battery without frills delivers high starting power, with regular maintenance it achieves a long service life and has excellent recycling properties. Our recommendation for an inexpensive standard motorcycle battery.

- **Reliable starting power at an excellent price.**
- **Replacement recommendation** for broken flooded battery.
- **Central degassing.**
- **Only to be installed upright,** as flooded battery with vent caps.


Size




Pos. of Terminal 1



Terminal G



Entgasung 6



As of 22.11.2026

KECKEISEN AKKUMULATOREN
Stefan Keckeisen Akkumulatoren e.K.
Europastraße 9
87700 Memmingen
Fon +49(0)8331 94444-0
Fax +49(0)8331 94444-9
info@intact-batterien.de
www.intact-batterien.de