



# intAct Start-Power

Calcium or hybrid battery (Ca/Ca or Sb/Ca)

Art.No.

## 53034SMF

Japancode

Y60-N30-A

|                            |                           |
|----------------------------|---------------------------|
| <b>Volt</b>                | 12V                       |
| <b>Capacity</b>            | 30 Ah (c20)               |
| <b>CCR -18°C (EN)</b>      | 300 A (EN)                |
| <b>Electrolyte</b>         | diluted sulphuric acid    |
| <b>Electrolyte density</b> | 1,28 +/- 0,01 Kg/l (25°C) |
| <b>Size (LxWxH)</b>        | 187 x 130 x 170 mm        |
| <b>Weight</b>              | 8 kg                      |
| <b>Pos. of Terminal</b>    | 1                         |
| <b>Terminal</b>            | G                         |
| <b>Bodenleiste</b>         | -                         |

## Usage




## Top performance at a great price

Developed for performance and extreme high-current capability at an absolutely perfect price-performance ratio. For almost all standard cars without many additional installations and other electrical consumers. Our recommendation for standard applications with low requirements and the best price-performance ratio.

- » **Powerful and reliable.**
- » **Double lid for increased leakage protection and gas condensation** (gaseous electrolyte condenses in the labyrinth lid and remains in the circuit).
- » **Filled and charged. Ready for immediate use.**
- » **Maintenance-free. No refilling of water necessary.**




Size



Pos. of Terminal 1



Terminal G



Bodenleiste -

As of 31.07.2025