



intact Start-Power Truck

Closed calcium battery (Ca/Ca) | filled and charged | maintenance-free

Art.No.

64036GUG

Volt	12V
Capacity	140 Ah (c20)
CCR -18°C (EN)	760 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/I (25° C)
Size (LxWxH)	513 x 189 x 223 mm
Weight	35,6 kg
Pos. of Terminal	3
Terminal	1
Bodenleiste	B13













Usage








Top performance at a good price


Developed for performance and extreme high-current capability at an absolutely perfect price-performance ratio. For almost all standard trucks without many additional installations and other electrical consumers. Our recommendation for standard applications with low requirements and the best priceperformance ratio.

- » Powerful and reliable.
- » Double lid for increased leakage protection and gas condensation(gaseous electrolyte condenses in the labyrinth lid and remains in the circuit).
- » Maintenance-free. No refilling of water necessary.
- » Filled and charged (GUG), ready for immediate use.
- » Available for trucks as a conventional wet starter battery, as well as **super heavy duty (SHD)** with glass fiber fleece separators vibration-resistant V3.
- » 30% more cycles compared to conventional commercial vehicle batteries.


Size








Terminal 1



Bodenleiste B13



As of 03.11.2025

