



# intAct AGM-Power - Marine & Leisure

Sealed AGM battery with grid plates | electrolyte fixed in fleece | filled and charged | absolutely maintenance-free

Art.No.

## AGM100

Volt	12V
Capacity	85 Ah (c5), 100 Ah (c20), 120 Ah (c100)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	358 x 175 x 233 mm
Weight	32,2 kg
Pos. of Terminal	0
Terminal	1
Bodenleiste	B13

### Usage




### Maintenance-free all-round

Completely sealed maintenance-free and leak-proof, therefore well suited for the interior. Uncomplicated power supply for hobby and leisure-time pursuits and smaller solar applications. Our recommendation for those looking for an affordable sealed supply battery.

- » 300 charging cycles according to IEC 254-1.
- » Longer service life than flooded lead-acid battery.
- » Low self-discharge.
- » VRLA battery with gas recombination and safety valves, where refilling is neither possible or necessary.
- » Sealed AGM battery with grid plates.
- » Leak-proof. Can also be installed at an angle, as the electrolyte is absorbed in glass fibre mats and the battery is tightly sealed.



Size



Pos. of Terminal 0



Terminal 1



Bodenleiste B13



As of 11.03.2026