



intAct AGM-Power - Marine & Leisure

Sealed AGM battery with grid plates | electrolyte fixed in fleece | filled and charged | absolutely maintenance-free

Art.No.

AGM114

Volt	12V
Capacity	110 Ah (c5), 114 Ah (c20), 136 Ah (c100)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	329 x 171 x 215 mm
Weight	34,5 kg
Pos. of Terminal	1
Terminal	F-M8
Bodenleiste	-



Usage




Maintenance-free all-round


Completely sealed maintenance-free and leak-proof, therefore well suited for the interior. Uncomplicated power supply for hobby and leisure-time pursuits and smaller solar applications. Our recommendation for those looking for an affordable sealed supply battery.

- » **300 charging cycles according to IEC 254-1.**
- » **Longer service life** than flooded lead-acid battery.
- » **Low self-discharge.**
- » **VRLA battery with gas recombination and safety valves**, where refilling is neither possible or necessary.
- » **Sealed AGM battery with grid plates.**
- » **Leak-proof.** Can also be installed at an angle, as the electrolyte is absorbed in glass fibre mats and the battery is tightly sealed.


Size



Pos. of Terminal 1



Terminal F-M8



Bodenleiste -

As of 13.01.2026