



intAct AGM-Power - Marine & Leisure

Sealed AGM battery with grid plates | electrolyte fixed in fleece | filled and charged | absolutely maintenance-free

Art.No.

AGM130

Volt	12V
Capacity	110 Ah (c5), 130 Ah (c20), 150 Ah (c100)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	513 x 189 x 223 mm
Weight	42 kg
Pos. of Terminal	3
Terminal	1
Bodenleiste	-

Usage




Maintenance-free all-round

Completely sealed maintenance-free and leak-proof, therefore well suited for the interior. Uncomplicated power supply for hobby and leisure-time pursuits and smaller solar applications. Our recommendation for those looking for an affordable sealed supply battery.


- » 300 charging cycles according to IEC 254-1.
- » Longer service life than flooded lead-acid battery.
- » Low self-discharge.
- » VRLA battery with gas recombination and safety valves, where refilling is neither possible or necessary.
- » Sealed AGM battery with grid plates.
- » Leak-proof. Can also be installed at an angle, as the electrolyte is absorbed in glass fibre mats and the battery is tightly sealed.




Size



Pos. of Terminal 3



Terminal 1



Bodenleiste -

As of 13.04.2026