



intAct AGM-Power

Sealed maintenance-free AGM battery with grid plates | electrolyte absorbed in glass fibre mats | wet charged

Art.No.

AGM260-06

| | |
|---------------------|--|
| Volt | 6V |
| Capacity | 220 Ah (c5), 260 Ah (c20), 278 Ah (c100) |
| CCR -18°C (EN) | - |
| Electrolyte | |
| Electrolyte density | |
| Size (LxWxH) | 262 x 181 x 281 mm |
| Weight | 35 kg |
| Pos. of Terminal | 0 |
| Terminal | F-M8 |
| Bodenleiste | - |



Usage




Maintenance-free all-round


Completely sealed maintenance-free and leak-proof, therefore well suited for the interior. Uncomplicated power supply for hobby and leisure-time pursuits and smaller solar applications. Our recommendation for those looking for an affordable sealed supply battery.

- » **300 charging cycles according to IEC 254-1.**
- » **Longer service life** than flooded lead-acid battery.
- » **Low self-discharge.**
- » **VRLA battery with gas recombination and safety valves,** where refilling is neither possible or necessary.
- » **Sealed AGM battery with grid plates.**
- » **Leak-proof.** Can also be installed at an angle, as the electrolyte is absorbed in glass fibre mats and the battery is tightly sealed.


Size



Pos. of Terminal 0



Terminal F-M8



Bodenleiste -

As of 18.08.2025