



# intAct AGM-Power - Marine & Leisure

Sealed AGM battery with grid plates | electrolyte fixed in fleece | filled and charged | absolutely maintenance-free

Art.No.

## AGM260-06

|                     |  |
|---------------------|--|
| Volt                | 6V                                       |
| Capacity            | 220 Ah (c5), 260 Ah (c20), 278 Ah (c100) |
| CCR -18°C (EN)      | -  |
| Electrolyte         | diluted sulphuric acid                   |
| Electrolyte density | 1,28 +/- 0,01 Kg/l (25° C)               |
| Size (LxWxH)        | 262 x 181 x 281 mm                       |
| Weight              | 70 kg                                    |
| Pos. of Terminal    | 0  |
| Terminal            | F-M8                                     |
| Bodenleiste         | -  |

### Usage




### Maintenance-free all-round

Completely sealed maintenance-free and leak-proof, therefore well suited for the interior. Uncomplicated power supply for hobby and leisure-time pursuits and smaller solar applications. Our recommendation for those looking for an affordable sealed supply battery.


- » 300 charging cycles according to IEC 254-1.
- » Longer service life than flooded lead-acid battery.
- » Low self-discharge.
- » VRLA battery with gas recombination and safety valves, where refilling is neither possible or necessary.
- » Sealed AGM battery with grid plates.
- » Leak-proof. Can also be installed at an angle, as the electrolyte is absorbed in glass fibre mats and the battery is tightly sealed.




Size



Pos. of Terminal 0



Terminal F-M8



Bodenleiste -

As of 13.04.2026