



intAct AGM-Power

Sealed maintenance-free AGM battery with grid plates | electrolyte absorbed in glass fibre mats | wet charged

Art.No.

AGM315-06

Volt	6V
Capacity	300 Ah (c5), 315 Ah (c20), 375 Ah (c100)
CCR -18°C (EN)	-
Electrolyte	
Electrolyte density	
Size (LxWxH)	312 x 180 x 359 mm
Weight	45 kg
Pos. of Terminal	0
Terminal	F-M8
Bodenleiste	-



Usage



Maintenance-free all-round


Completely sealed maintenance-free and leak-proof, therefore well suited for the interior. Uncomplicated power supply for hobby and leisure-time pursuits and smaller solar applications. Our recommendation for those looking for an affordable sealed supply battery.

- » **300 charging cycles according to IEC 254-1.**
- » **Longer service life** than flooded lead-acid battery.
- » **Low self-discharge.**
- » **VRLA battery with gas recombination and safety valves**, where refilling is neither possible or necessary.
- » **Sealed AGM battery with grid plates.**
- » **Leak-proof.** Can also be installed at an angle, as the electrolyte is absorbed in glass fibre mats and the battery is tightly sealed.


Size

Kasten: **AGM315-06**

Pos. of Terminal 0



Terminal F-M8



Bodenleiste -

As of 18.08.2025