



## intAct AGM-Power - Marine & Leisure

Sealed AGM battery with grid plates | electrolyte fixed in fleece | filled and charged | absolutely maintenance-free

Art.No.

## AGM55

| Volt                | 12V                                   |
|---------------------|---------------------------------------|
| Capacity            | 50 Ah (c5), 55 Ah (c20), 70 Ah (c100) |
| CCR -18°C (EN)      | -                                     |
| Electrolyte         | diluted sulphuric acid                |
| Electrolyte density | 1,28 +/- 0,01 Kg/l (25° C)            |
| Size (LxWxH)        | 242 x 175 x 190 mm                    |
| Weight              | 16,7 kg                               |
| Pos. of Terminal    | 0                                     |
| Terminal            | 1                                     |
| Bodenleiste         | B13                                   |











## Usage




## Maintenance-free all-round


Completely sealed maintenance-free and leak-proof, therefore well suited for the interior. Uncomplicated power supply for hobby and leisure-time pursuits and smaller solar applications. Our recommendation for those looking for an affordable sealed supply battery.

- » 300 charging cycles according to IEC 254-1.
- » Longer service life than flooded lead-acid battery.
- » Low self-discharge.
- » VRLA battery with gas recombination and safety valves, where refilling is neither possible or necessary.
- » Sealed AGM battery with grid plates.
- » Leak-proof. Can also be installed at an angle, as the electrolyte is absorbed in glass fibre mats and the battery is tightly sealed.


Size




Pos. of Terminal O



Terminal 1



Bodenleiste B13



As of 29.11.2025

