



intAct Start-Stop-Power AGM

Sealed AGM battery | electrolyte bound in fleece | filled and charged | absolutely maintenance-free

Art.No.

AGM80SS

Volt	12V
Capacity	80 Ah (c20)
CCR -18°C (EN)	800 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	315 x 175 x 190 mm
Weight	22,8 kg
Pos. of Terminal	0
Terminal	1
Bodenleiste	B13

Usage




Start. Stop. Keep charging.

Enables a high number of engine starts and supplies all consumers when the motor stops. Perfect for taxis, medium and high-end cars, SUVs and trucks with start-stop systems and micro-hybrids with brake energy recovery (recuperation). Our recommendation for start-stop vehicles with high energy demand and micro-hybrids with recuperation.


- » Excellent starting characteristics even at low charge level.
- » Higher cycle stability and cold start performance than a standard starter battery of same case size. Resulting in a longer life expectancy.
- » Fantastic recharging behaviour in the partial charge range.
- » Also for vehicles with high energy requirements and/or a lot of additional equipment.
- » Double lid with safety valve (VRLA), gas recombination and backfire protection. Leak-proof.




Size




Pos. of Terminal 0



Terminal 1



Bodenleiste B13



As of 10.02.2026