



intAct Active-Power GEL

Sealed maintenance-free GEL battery with grid plates | electrolyte thickened into a gel-like mass | wet charged

Art.No.

AP-GEL-210

Volt	12V
Capacity	160AH (c5), 210 AH (c20), 230 AH (c100)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	518 x 276 x 242 mm
Weight	67 kg
Pos. of Terminal	3
Terminal	1
Bodenleiste	-

Usage




Maintain-free and uncomplicated

With low self-discharge for the seasonal operation of additional consumers on boats or in mobile homes. Robust power-supply for recreational and smaller solar applications. Our recommendation for anyone looking for a more cycle-resistant, spill-proof supply battery.

- » **Multifunctional battery for increased cyclical use.** 500 cycles according to IEC 254-1.
- » **Longer life expectancy** than conventional lead-acid batteries.
- » **Extremely resistant to vibration.**
- » **Sealed maintenance-free.** VRLA battery with gas recombination and safety valves, where refilling is neither possible nor necessary.
- » Wet charged. **Ready to use.**



Size



Pos. of Terminal 3



Terminal 1



Bodenleiste -

As of 02.04.2025