



## intAct Block-Power

Sealed AGM battery with grid plates | electrolyte absorbed in glass fibre mats | filled and charged | absolutely maintenance-free

Art.No.

### BP12-120

|                     |                             |
|---------------------|-----------------------------|
| Volt                | 12V                         |
| Capacity            | 132,2 Ah(c20), 120 Ah (c10) |
| CCR -18°C (EN)      | -                           |
| Electrolyte         | diluted sulphuric acid      |
| Electrolyte density | 1,28 +/- 0,01 Kg/l (25° C)  |
| Size (LxWxH)        | 408 x 177 x 225 mm          |
| Weight              | 36,6 kg                     |
| Pos. of Terminal    | 1                           |
| Terminal            | F-M8                        |
| Bodenleiste         | -                           |



### Usage




### Ready for many uses

The intAct Block-Power AGM batteries are versatile - whether as **power or supply batteries** for hobby applications or for hazard alarm, UPS and emergency lighting systems. They offer a **reliable power supply** in standby mode, are absolutely maintenance-free, leak-proof and have **low self-discharge**. Thanks to their **longevity and high performance**, they guarantee maximum safety and reliability in various areas of application.


#### Advantages at a glance:

- » Versatile use for **drive & supply**
- » **Durable & powerful**
- » **Reliable power supply** in standby mode
- » **Maintenance-free & leak-proof**
- » **Low self-discharge**
- » **Partially VDS-approved**


Size



Pos. of Terminal 1



Terminal F-M8



Bodenleiste -

As of 18.06.2026