



# intAct Block-Power

Sealed maintenance-free AGM battery with grid plates | electrolyte absorbed in glass fibre mats| wet charged

Art.No.

## BP12-35

Volt	12V
Capacity	35 Ah (c20), 32,6 Ah (c10)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	195 x 130 x 167 mm
Weight	10,5 kg
Pos. of Terminal	1
Terminal	F-M6
Bodenleiste	-

### Usage




## Ready for many uses


Durable, powerful series for hazard detection systems and absolutely reliable energy storage for safety power supply, safety lighting and various hobby applications. Our recommendation for all safety applications and any application to which it fits from the specifications.

- » **Quickly ready in stand-by mode.**
- » Low self-discharge.
- » Sealed block batteries with grid plates and fleece separators (AGM).
- » Absolutely maintenance-free and leak-proof.
- » **In three versions:**
  - Block Power**
    - Medium cyclic use
    - BP12-35 **extra cyclic use**
    - **3 - 5 years design life** according to Eurobat (General Purpose)
    - BP12-50, BP12-75 **extra cycle resistant**
    - **10 to 12 years Designlife** according to Eurobat (Longlife)


Size



Pos. of Terminal 1



Terminal F-M6



Bodenleiste -

As of 15.06.2025