



# intAct Block-Power

Sealed AGM battery with grid plates | electrolyte absorbed in glass fibre mats | filled and charged | absolutely maintenance-free

Art.No.

## BP12-60

Volt	12V
Capacity	64,8 Ah (c20), 60 Ah (c10)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	276 x 174 x 190 mm
Weight	19,7 kg
Pos. of Terminal	0
Terminal	F-M6
Bodenleiste	-



### Usage




## Ready for many uses

The intAct Block-Power AGM batteries are versatile - whether as **power or supply batteries** for hobby applications or for hazard alarm, UPS and emergency lighting systems. They offer a **reliable power supply** in standby mode, are absolutely maintenance-free, leak-proof and have **low self-discharge**. Thanks to their **longevity and high performance**, they guarantee maximum safety and reliability in various areas of application.


### Advantages at a glance:

- » Versatile use for **drive & supply**
- » **Durable & powerful**
- » **Reliable power supply** in standby mode
- » **Maintenance-free & leak-proof**
- » **Low self-discharge**
- » **Partially VDS-approved**


Size



Pos. of Terminal 0



Terminal F-M6



Bodenleiste -

As of 18.06.2026