Datasheet

intAct Block-Power

Sealed AGM battery with grid plates | electrolyte absorbed in glass fibre mats | filled and charged | absolutely maintenance-free

Art.No.

BP12-65

Certified

VDS

Volt	12V
Capacity	68,2 Ah (c20), 65 Ah (c10)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	348 x 167 x 178 mm
Weight	21 kg
Pos. of Terminal	**1**
Terminal	**F-M6**
Bodenleiste	**-**

Usage

Ready for many uses

The **intAct Block-Power** AGM batteries are versatile - whether as **power or supply batteries** for hobby applications or for hazard alarm, UPS and emergency lighting systems. They offer a **reliable power supply** in standby mode, are absolutely maintenance-free, leak-proof and have **low self-discharge**. Thanks to their **longevity and high performance**, they guarantee maximum safety and reliability in various areas of application.

Advantages at a glance:

- Versatile use for **drive & supply**
- **Durable & powerful**
- **Reliable power supply** in standby mode
- **Maintenance-free & leak-proof**
- **Low self-discharge**

Size



Pos. of Terminal 1



Terminal F-M6



Bodenleiste -

As of 11.10.2026

KECKEISEN AKKUMULATOREN
Stefan Keckeisen Akkumulatoren e.K.
Europastraße 9
87700 Memmingen
Fon +49(0)8331 94444-0
Fax +49(0)8331 94444-9
info@intact-batterien.de
www.intact-batterien.de