



## intAct BackUp-Power

Sealed calcium battery (Ca/Ca) | electrolyte absorbed in glass fibre mats (AGM) | filled and charged | absolutely maintenance-free

Art.No.

**BU01.2**

Volt	12V
Capacity	1,2 Ah (c20)
CCR -18°C (EN)	18 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	97 x 43 x 58 mm
Weight	0,5 kg
Pos. of Terminal	4
Terminal	S-4.8
Bodenleiste	-



### Usage




### Support for the starter battery


Supplies consumers in certain types of vehicles and keeps them charged during the start-up, thus protecting the electronics. Our recommendation as a reliable alternative to the original installed back-up battery.

- » **Increased cold start performance.**
- » **Longer life expectancy.** Three times more cycle resistant than conventional starter batteries.
- » Wet charged. **Ready to use.**
- » **Sealed valve-regulated battery (VRLA)** with gas recombination.
- » **Sealed maintenance-free and leak-proof.**
- » **Electrolyte absorbed in glass fibre mat.**
- » **Lead-calcium alloy grid plates.**


### Size



### Pos. of Terminal 4



### Terminal S-4.8



### Bodenleiste -

As of 27.01.2026