



# intAct BackUp-Power

Sealed calcium battery (Ca/Ca) | electrolyte absorbed in glass fibre mats (AGM) | filled and charged | absolutely maintenance-free

Art.No.

**BU14**

Volt	12V
Capacity	14 Ah (c20)
CCR -18°C (EN)	80 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	151 x 98 x 101 mm
Weight	3,85 kg
Pos. of Terminal	3
Terminal	Schraubanschluss
Bodenleiste	-



## Usage




## Support for the starter battery


Supplies consumers in certain types of vehicles and keeps them charged during the start-up, thus protecting the electronics. Our recommendation as a reliable alternative to the original installed back-up battery.

- » Increased cold start performance.
- » Longer life expectancy. Three times more cycle resistant than conventional starter batteries.
- » Wet charged. Ready to use.
- » Sealed valve-regulated battery (VRLA) with gas recombination.
- » Sealed maintenance-free and leak-proof.
- » Electrolyte absorbed in glass fibre mat.
- » Lead-calcium alloy grid plates.


### Size



### Pos. of Terminal 3



### Terminal Schraubanschluss



### Bodenleiste -

As of 27.01.2026