



# intAct Traktion-Power Deepcycle AGM

Sealed AGM battery with grid plates | electrolyte fixed in fleece | filled and charged | absolutely maintenance-free

Art.No.

## DC12-45AGM

Volt	12V
Capacity	45 Ah (c5), 52 Ah (c20)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric aci
Electrolyte density	
Size (LxWxH)	224 x 120 x 175 mm
Weight	12,6 kg
Pos. of Terminal	3
Terminal	F-M5
Bodenleiste	-



### Usage





### Robust and enduring

AGM-based for high currents and deep charge cycles. Our recommendation if you want an enduring, absolutely maintenance-free battery for electric vehicles or lifting platforms.

- » **Very high life expectancy.** 700 cycles according to IEC 254-1 for heavy cyclic use.
- » **Absolutely maintenance-free.** VRLA battery with gas recombination and safety valves, where refilling is not possible and not necessary.
- » **Constant power quality** throughout the discharge process even at high currents.
- » **Longer life** than wet lead-acid battery.
- » **Shorter charging time** than wet lead-acid battery.
- » **Low self-discharge.** Loses less than 3% charge per month.
- » **Vibration resistant AGM battery** with robust grids and strong fleece separators.
- » **Reinforced grid plates** with higher performance active material **for deep cycle applications.**
- » **Temperature and corrosion resistant case.**
- » **Can also be installed horizontally.**
- » **Leak-proof.**

Size  
Kasten: DC12-45AGM



Bodenleiste -

As of 30.04.2026