



intAct Start-Stop-Power EFB

Maintenance-free EFB (Enhanced Flooded Battery) | wet charged

Art.No.

EFB75SS

Volt	12V
Capacity	75 Ah (c20)
CCR - 18°C (EN)	730 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	315 x 175 x 175 mm
Weight	18,6 kg
Pos. of Terminal	0
Terminal	1
Bodenleiste	B13




Usage

600 D My O TAXI

Start. Stop. Keep charging.

For small and medium-sized cars with start-stop systems and micro-hybrids with energy recovery. Enables an increased number of engine starts and supplies all consumers when the engine stops. Our recommendation if an EFB was installed in the start-stop system and you do not want to upgrade to AGM.

- » Excellent starting characteristics even at low charge level.
- » Higher cycle stability and cold start performance than standard starter battery in same box size. Therefore longer life expectancy.
- » Fantastic recharging behaviour in the partial charge range.
- » Maintenance-free battery with lead-calcium-tin grids.
- » Double lid with central degassing and backfire protection. Leak-proof.



MULATOREN

Stefan Keckeisen Akkumulatoren e.K. Europastraße 9 87700 Memmingen Fon +49(0)833194444-0 Fax +49(0)833194444-9

info@intact-batterien.de www.intact-batterien.de