



# intAct Bike-Power GEL HVT-HD

Sealed maintenance-free GEL with extra compressed plate packs | electrolyte thickened into a gel-like mass

Art.No.

## GEL-HVT-01

Japancode

YTX20HL-BS, YTX20L-BS, YTX20HL-BS-PW, YTX20HL, YTX20L, , GYZ20L, GYZ20HL, 65989-97A

Volt	12V
Capacity	20 Ah (c20)
CCR -18°C (EN)	350 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28+/- 0,01 Kg/l (25°)
Size (LxWxH)	175 x 87 x 155 mm
Weight	6,4 kg
Pos. of Terminal	0
Terminal	M
Bodenleiste	-



### Usage




## Extremely vibration-resistant power package


Low self-discharge and particularly high currents make this battery the perfect choice for Harleys and other high-capacity bikes with lots of extra equipment. Our recommendation for motorcycles with a lot of consuming equipment and powerful engines.

- » Perfect for **Harleys** and other bikes with **high-capacity 2-cylinder engines**.
- » **Highest cold cranking aper:** For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- » **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » **Robust housing made of impact-resistant plastic.** For heavy mechanical stress.
- » **Leak-proof. Can be installed at an angle** because the electrolyte is thickened into a gel-like mass.
- » **Sealed maintenance-free.**


Size



Pos. of Terminal 0



Terminal M



Bodenleiste -

As of 01.08.2025