



intAct Bike-Power GEL HVT-HD

Sealed maintenance-free GEL with extra compressed plate packs | electrolyte thickened into a gel-like mass

Art.No.

GEL-HVT-02

Japancode

GYZ32HL, YB30L-B, YIX30HL-BS, YIX30L-BS, YIX30L-PW, YIX30L

Volt	12V
Capacity	32 AH (c20)
CCR -18°C(EN)	445 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28+/- 0,01 Kg/l (25°)
Size (LxWxH)	169 x 131 x 174 mm
Weight	10,4 kg
Pos. of Terminal	0
Terminal	Schraubanschluss
Bodenleiste	-

Usage




Extremely vibration-resistant power package

Low self-discharge and particularly high currents make this battery the perfect choice for Harleys and other high-capacity bikes with lots of extra equipment. Our recommendation for motorcycles with a lot of consuming equipment and powerful engines.


- » Perfect for **Harleys** and other bikes with **high-capacity 2-cylinder engines**.
- » **Highest cold cranking aper:** For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- » **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » **Robust housing made of impact-resistant plastic.** For heavy mechanical stress.
- » **Leak-proof. Can be installed at an angle** because the electrolyte is thickened into a gel-like mass.
- » **Sealed maintenance-free.**




Size



Pos. of Terminal 0



Terminal Schraubanschluss



Bodenleiste -

As of 03.04.2025