



intAct Bike-Power GEL HVT-HD

Sealed maintenance-free GEL with extra compressed plate packs | electrolyte thickened into a gel-like mass

Art.No.

GEL-HVT-03

Japancode

YTX14L-BS, 65958-04A

| | |
|---------------------|-------------------------|
| Volt | 12V |
| Capacity | 14 Ah (c20) |
| CCR -18°C (EN) | 255 A (EN) |
| Electrolyte | diluted sulphuric acid |
| Electrolyte density | 1,28+/- 0,01 Kg/l (25°) |
| Size (LxWxH) | 150 x 87 x 145 mm |
| Weight | 4,6 kg |
| Pos. of Terminal | 0 |
| Terminal | Schraubanschluss |
| Bodenleiste | - |



Usage




Extremely vibration-resistant power package


Low self-discharge and particularly high currents make this battery the perfect choice for Harleys and other high-capacity bikes with lots of extra equipment. Our recommendation for motorcycles with a lot of consuming equipment and powerful engines.

- » Perfect for **Harleys** and other bikes with **high-capacity 2-cylinder engines**.
- » **Highest cold cranking aper:** For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- » **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » **Robust housing made of impact-resistant plastic.** For heavy mechanical stress.
- » **Leak-proof. Can be installed at an angle** because the electrolyte is thickened into a gel-like mass.
- » **Sealed maintenance-free.**


Size



Pos. of Terminal 0



Terminal Schraubanschluss



Bodenleiste -

As of 13.12.2025