



# intAct Bike-Power GEL HVT-HD

Sealed maintenance-free GEL with extra compressed plate packs | electrolyte thickened into a gel-like mass

Art.No.

## GEL-HVT-03

Japancode

YTX14L-BS

Volt	12V
Capacity	14 AH (c20)
CCR -18°C(EN)	255 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28+/- 0,01 Kg/l(25°)
Size (LxWxH)	150 x 87 x 145 mm
Weight	4,6 kg
Pos. of Terminal	0
Terminal	Schraubanschluss
Bodenleiste	-

### Usage




## Extremely vibration-resistant power package

Low self-discharge and particularly high currents make this battery the perfect choice for Harleys and other high-capacity bikes with lots of extra equipment. Our recommendation for motorcycles with a lot of consuming equipment and powerful engines.


- » Perfect for **Harleys** and other bikes with **high-capacity 2-cylinder engines**.
- » **Highest cold cranking aper:** For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- » **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » **Robust housing made of impact-resistant plastic.** For heavy mechanical stress.
- » **Leak-proof. Can be installed at an angle** because the electrolyte is thickened into a gel-like mass.
- » **Sealed maintenance-free.**




Size



Pos. of Terminal 0



Terminal Schraubanschluss



Bodenleiste -

As of 03.04.2025