



# intAct Bike-Power GEL HVT-HD

Sealed maintenance-free GEL with extra compressed plate packs | electrolyte thickened into a gel-like mass | absolutely maintenance-free

Art.No.

## GEL-HVT-03

Japancode

65958-04A, YTX14L-BS

Volt	12V
Capacity	14 Ah (c20)
CCR -18°C(EN)	255 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28+/- 0,01 Kg/l(25°)
Size (LxWxH)	150 x 87 x 145 mm
Weight	4,6 kg
Pos. of Terminal	0
Terminal	Schraubanschluss
Bodenleiste	-



### Usage




## Extremely vibration-resistant power package

The **intAct Bike-Power HVT GEL** series offers the ideal energy supply for **high-capacity two-cylinder motorcycles** such as Harley Davidson. The electrolyte in these **GEL motorcycle batteries** is gel-bound, which ensures **absolute leakproofness** and makes the battery particularly resistant to **vibrations and shocks**. With **higher starting performance** and **lower self-discharge**, the battery starts reliably even after long periods of inactivity. Perfectly suited for **off-road motorcycles, jet skis, snowmobiles** and many other seasonally used vehicles.


### Advantages at a glance:

- » **High power reserve**, reliable even after long downtimes
- » **Extremely vibration-resistant** thanks to compact plate packs
- » **Robust housing** made of impact-resistant plastic for optimum protection
- » **Low self-discharge**, ideal for seasonal use
- » **Maintenance-free & leak-proof** thanks to GEL technology
- » **Sealed ex works**, Ready for immediate use


Size



Pos. of Terminal 0



Terminal Schraubanschluss



Bodenleiste -

As of 13.06.2026