



# intAct Bike-Power GEL HVT-HD

Sealed maintenance-free GEL with extra compressed plate packs | electrolyte thickened into a gel-like mass

Art.No.

## GEL-HVT-08

Japancode

YTX14H-BS, YTX14-BS, YTX14, YTX14H

|                     |                        |
|---------------------|------------------------|
| Volt                | 12V                    |
| Capacity            | 14 AH (c20)            |
| CCR -18°C(EN)       | 255 A (EN)             |
| Electrolyte         | diluted sulphuric acid |
| Electrolyte density | 1,28+/- 0,01 Kg/l(25°) |
| Size (LxWxH)        | 150 x 87 x 145 mm      |
| Weight              | 4,6 kg                 |
| Pos. of Terminal    | 1                      |
| Terminal            | Schraubanschluss       |
| Bodenleiste         | -                      |



### Usage




## Extremely vibration-resistant power package


Low self-discharge and particularly high currents make this battery the perfect choice for Harleys and other high-capacity bikes with lots of extra equipment. Our recommendation for motorcycles with a lot of consuming equipment and powerful engines.

- » Perfect for **Harleys** and other bikes with **high-capacity 2-cylinder engines**.
- » **Highest cold cranking aper:** For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- » **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » **Robust housing made of impact-resistant plastic.** For heavy mechanical stress.
- » **Leak-proof. Can be installed at an angle** because the electrolyte is thickened into a gel-like mass.
- » **Sealed maintenance-free.**


Size



Pos. of Terminal 1



Terminal Schraubanschluss



Bodenleiste -

As of 03.04.2025