



intAct Bike-Power AGM HVT

Sealed maintenance-free AGM battery with heavily compressed plate packs | electrolyte absorbed in glass fibre separators

Art.No.

HVT-02

YIX30L-BS, YIX30HL-BS, YB30L-B, YIX30L-PW, YIX30L, 66010-97A

Volt	12V
Capacity	30 Ah (c20)
CCR -18°C (EN)	380 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,32 +/- 0,01Kg/I(25°)
Size (LxWxH)	169 x 131 x 174 mm
Weight	10,2 kg
Pos. of Terminal	0
Terminal	M
Bodenleiste	-



















Usage



Extremely vibration-resistant design


The durable energy bundle absorbs the strongest shocks from Harleys and other high-capacity bikes and also starts twowheelers with high electrical energy requirements (e.g. with ABS). Our recommendation for motorcycles that need a lot of starting power and of course with strong vibrations.

- » Perfect for Harleys and other bikes with high-capacity 2cylinder engines.
- » Highest cold cranking amper: For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- » Extremely vibration-resistant. Plate packs compressed and precisely fitted into the battery box.
- » Robust housing made of impact-resistant plastic. For heavy mechanical stress.
- » Leak-proof. Can be installed at an angle, as the electrolyte is absorbed in glass fibre mat.
- » Sealed maintenance-free.


Size



Pos. of Terminal O



Terminal M



Bodenleiste -

As of 24.11.2025

