



intAct Bike-Power AGM HVT

Sealed maintenance-free AGM battery with heavily compressed plate packs | electrolyte absorbed in glass fibre separators | absolutely maintenance-free

Art.No.

HVT-02

Japancode

66010-97A, YIX30L-BS, YIX30HL-BS, YB30L-B, YIX30L-PW, YIX30L

| | |
|----------------------------|------------------------|
| Volt | 12V |
| Capacity | 30 Ah (c20) |
| CCR -18°C(EN) | 380 A (EN) |
| Electrolyte | diluted sulphuric acid |
| Electrolyte density | 1,32 +/- 0,01Kg/l(25°) |
| Size (LxWxH) | 169 x 131 x 174 mm |
| Weight | 10,2 kg |
| Pos. of Terminal | 0 |
| Terminal | M |
| Bodenleiste | - |

Usage




Extremely vibration-resistant design

The durable energy bundle absorbs the strongest shocks from Harleys and other high-capacity bikes and also starts two-wheelers with high electrical energy requirements (e.g. with ABS). Our recommendation for motorcycles that need a lot of starting power and of course with strong vibrations.


- » Perfect for **Harleys** and other bikes with **high-capacity 2-cylinder engines**.
- » **Highest cold cranking amper:** For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- » **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » **Robust housing made of impact-resistant plastic.** For heavy mechanical stress.
- » **Leak-proof. Can be installed at an angle,** as the electrolyte is absorbed in glass fibre mat.
- » **Sealed maintenance-free.**




Size



Pos. of Terminal 0



Terminal M



Bodenleiste -

As of 11.03.2026