



intAct Bike-Power AGM HVT

Sealed maintenance-free AGM battery with heavily compressed plate packs | electrolyte absorbed in glass fibre separators | absolutely maintenance-free

Art.No.

HVT-03

Japancode
65958-04A, YTX14L-BS

| | |
|---------------------|------------------------|
| Volt | 12V |
| Capacity | 14 Ah (c20) |
| CCR -18°C(EN) | 250 A (EN) |
| Electrolyte | diluted sulphuric acid |
| Electrolyte density | 1,32 +/- 0,01Kg/l(25°) |
| Size (LxWxH) | 150 x 87 x 145 mm |
| Weight | 5 kg |
| Pos. of Terminal | 0 |
| Terminal | Schraubanschluss |
| Bodenleiste | - |



Usage




Extremely vibration-resistant design

The intAct Bike-Power AGM HVT series has been specially developed for high-capacity motorcycles **such as Harleys**. Thanks to AGM technology, the electrolyte is bound in a glass fiber fleece, which makes the battery absolutely leak-proof, extremely vibration-resistant and particularly durable. It offers more starting power than conventional motorcycle batteries and low self-discharge,** so that it starts reliably even after long periods of non-use. Perfect for powerful machines, but also for off-road motorcycles, jet skis, snowmobiles or lawnmower tractors.


Advantages at a glance:

- » **High power reserve**, delivers strong starting power even when partially discharged
- » **Maximum vibration resistance** due to tightly packed plate packs
- » **Robust housing** made of impact-resistant plastic for extra protection
- » **Low self-discharge**, ideal for seasonal vehicles
- » **Fast recharging**, ideal for short journeys
- » **Maintenance-free & leak-proof** thanks to AGM technology
- » **Sealed ex works**, Ready for immediate use.
Except HVT-10: It comes dry-charged, an acid pack is not included.


Size



Pos. of Terminal 0



Terminal Schraubanschluss



Bodenleiste -

As of 08.07.2026