



# intAct Bike-Power AGM HVT

Sealed maintenance-free AGM battery with heavily compressed plate packs | electrolyte absorbed in glass fibre separators

Art.No.

## HVT-04

Japancode

YB16L-B, YB16CL-B, 65989-90B

Volt	12V
Capacity	22 Ah (c20)
CCR -18°C (EN)	300 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,32 +/- 0,01Kg/l (25°)
Size (LxWxH)	176 x 101 x 156 mm
Weight	7 kg
Pos. of Terminal	0
Terminal	M
Bodenleiste	-



## Usage




## Extremely vibration-resistant design


The durable energy bundle absorbs the strongest shocks from Harleys and other high-capacity bikes and also starts two-wheelers with high electrical energy requirements (e.g. with ABS). Our recommendation for motorcycles that need a lot of starting power and of course with strong vibrations.

- » Perfect for **Harleys** and other bikes with **high-capacity 2-cylinder engines**.
- » **Highest cold cranking amper:** For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- » **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » **Robust housing made of impact-resistant plastic.** For heavy mechanical stress.
- » **Leak-proof. Can be installed at an angle,** as the electrolyte is absorbed in glass fibre mat.
- » **Sealed maintenance-free.**


Size



Pos. of Terminal 0



Terminal M



Bodenleiste -

As of 13.12.2025