



intAct Bike-Power AGM HVT

Sealed maintenance-free AGM battery with heavily compressed plate packs | electrolyte absorbed in glass fibre separators

Art.No.

HVT-05

Japancode

YB16-B, 65991-82B

Volt	12V
Capacity	22 Ah (c20)
CCR -18°C (EN)	300 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,32 +/- 0,01Kg/I(25°)
Size (LxWxH)	176 x 101 x 156 mm
Weight	7 kg
Pos. of Terminal	1
Terminal	М
Bodenleiste	-



















Usage



Extremely vibration-resistant design


The durable energy bundle absorbs the strongest shocks from Harleys and other high-capacity bikes and also starts two-wheelers with high electrical energy requirements (e.g. with ABS). Our recommendation for motorcycles that need a lot of starting power and of course with strong vibrations.

- » Perfect for Harleys and other bikes with high-capacity 2cylinder engines.
- **>> Highest cold cranking amper:** For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » Robust housing made of impact-resistant plastic. For heavy mechanical stress.
- » Leak-proof. Can be installed at an angle, as the electrolyte is absorbed in glass fibre mat.
- » Sealed maintenance-free.


Size



Pos. of Terminal 1



Terminal M



Bodenleiste -

As of 13.12.2025

