



intAct Bike-Power AGM HVT

Sealed maintenance-free AGM battery with heavily compressed plate packs | electrolyte absorbed in glass fibre separators | absolutely maintenance-free

Art.No.

HVT-06

Japancode

66010-82B, YTX24HL-BS, Y50-N18L-A3

Volt	12V
Capacity	23 Ah (c20)
CCR -18°C(EN)	350 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,32 +/- 0,01Kg/l(25°)
Size (LxWxH)	205 x 87 x 162 mm
Weight	7,9 kg
Pos. of Terminal	0
Terminal	M
Bodenleiste	-



Usage




Extremely vibration-resistant design

The intAct Bike-Power AGM HVT series has been specially developed for high-capacity motorcycles **such as Harleys**. Thanks to AGM technology, the electrolyte is bound in a glass fiber fleece, which makes the battery absolutely leak-proof, extremely vibration-resistant and particularly durable. It offers more starting power than conventional motorcycle batteries and low self-discharge,** so that it starts reliably even after long periods of non-use. Perfect for powerful machines, but also for off-road motorcycles, jet skis, snowmobiles or lawnmower tractors.


Advantages at a glance:

- » High power reserve, delivers strong starting power even when partially discharged
- » Maximum vibration resistance due to tightly packed plate packs
- » Robust housing made of impact-resistant plastic for extra protection
- » Low self-discharge, ideal for seasonal vehicles
- » Fast recharging, ideal for short journeys
- » Maintenance-free & leak-proof thanks to AGM technology
- » Sealed ex works, Ready for immediate use


Size



Pos. of Terminal 0



Terminal M



Bodenleiste -

As of 24.05.2026