



## intact Premium-Power Truck

Closed EFB battery | vibration-proof according to V4 standard | filled and charged | maintenance-free

Art.No.

## PP140MF

| Volt                | 12V                        |
|---------------------|----------------------------|
| Capacity            | 140 AH (c20)               |
| CCR -18°C (EN)      | 800 A (EN)                 |
| Electrolyte         | diluted sulphuric acid     |
| Electrolyte density | 1,28 +/- 0,01 Kg/l (25° C) |
| Size (LxWxH)        | 513 x 189 x 223 mm         |
| Weight              | 39,7 kg                    |
| Pos. of Terminal    | 3                          |
| Terminal            | 1                          |
| Bodenleiste         | -                          |







## Usage







## Truck battery with 30 % extra starting power


This starter battery for trucks and commercial vehicles is ideally suited for highly equipped vehicles with many electrical consumers or those used in urban delivery traffic or on construction sites. With minimal self-discharge, particularly safe and temperature-resistant. \*\*Our recommendation for vehicles with a lot of equipment, especially if short journeys are often

- » 30 % more starting power than standard starter batteries with the same box size.
- » Fast charging. Up to 1.5 times faster charging\*\* thanks to faster current consumption than standard starter batteries with the same box size.
- » Double lid for increased leakage protection and gas condensation\*\* (gaseous electrolyte condenses in the labyrinth lid and remains in the circuit).


Size



Pos. of Terminal 3



Terminal 1



Bodenleiste -

As of 03.04.2025

