



# intAct Flooded-Power - Marine & Leisure

Closed lead-acid battery with reinforced grid plates | filled and charged | low maintenance

Art.No.

## SP128GUG

Volt	12V
Capacity	90 Ah (c5), 114 Ah (c20), 128 Ah (c100)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	330 x 172 x 242 mm
Weight	25 kg
Pos. of Terminal	1
Terminal	DT
Bodenleiste	-

### Usage




## intAct Flooded-Power - Marine & Leisure

Reliable wet-cell battery with good capacity absorption, high capacity reserves and proven technology - ideal for use in leisure, hobby and on the water.


- » **Filled and charged. Ready for immediate use.**
- » **Light cyclical use.** 300 cycles according to IEC 254-1.
- » **Reinforced special-insulation grid plates** with high mass utilisation for maximum capacity reserves.
- » Robust, technically uncomplicated, mature technology for **applications with low, reliable power requirements.**
- » **Ideal for stand-by operation.**
- » **Excellent value for money.** Durable, safe and reliable.



Size



Pos. of Terminal 1



Terminal DT



Bodenleiste -

As of 19.04.2026